



BL-C131 WIRELESS

Panasonic
ideas for life

OVERVIEW

The wireless **Panasonic BL-C131** IP network camera is ideal to monitor indoors areas. It integrates a 10x digital zoom enabling an accurate view of small details at home or in your business. Thanks to the built-in Microphone, the sounds picked up, can be heard through the PC.

Main features:

- Capture suspicious sounds: Built-in Microphone
- Informs you immediately of changes: Alerting yourself when changes occur
- Monitors large rooms entirely: Remote Pan/Tilt and zoom control
- Simultaneous MPEG-4 and JPEG

TECHNICAL SPECIFICATIONS

Server

Video compression: JPEG (3 levels), MPEG4
Video resolution: 640x480, 320x240 (default), 192x144
Frame rate: Max. 30 fps. (640x480, 320x24, 192x144)
Maximum access users: 30
Supported protocols IPv4 / IPv6 Dual-Stack
 IPv4: TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, UPnP, SMTP Authentication, RTP, RTSP, RTCP.
 IPv6: TCP, UDP, IP, HTTP, FTP, SMTP, DNS, ICMPv6, POP3, NDP, NTP, RTP, RTSP, RTCP

Buffered image Aprox. 250 images (20x240)
 Standard image quality

Camera

Zoom: 10 x digital zoom (by areas)
Image sensor: 1/6-inch CMOS sensor, 320,000 pixels.
White balance: Auto/Manual/hold
Illumination: 10-100,000 lx (3 – 100,000 lx in colour night view mode).
Focus: Fixed 0.3 m to ~
Lens Brightness: F2.8
Exposure: Auto

Angle of view: Horizontal 49°; Vertical 37°

Exposure: Auto

Terminal

Interface: Ethernet 10Base-T/100Base-TX

Audio

Audio communication: Half-duplex on-way comm
Audio play Method Play with ActiveX
Audio bandwidth 300 Hz-3.4kHz
Audio input Built-in Microphone

General

Dimensions 98 mm x 74 mm x 73 mm
Display: Power / Network communication / Camera operation / Ethernet link

Weight: 210 gr.

Power supply Input 100 – 240 V AC, output 9VDC

Consumption 4.0W

Temperature: Operating: +5° a + 40°C

Humidity: 20 % - 80% (no condensation)

Wireless

Standards 802.11 b/g

Antenna Diversity

Number of channels 13 ch